

# **Multivariate Fiat-Shamir signatures**

SLMath summer school:

Introduction to Quantum-Safe Cryptography (IBM Zurich)

Simona Samardjiska

July, 2024

Institute for Computing and Information Sciences Radboud University

### Recall the MQ problem from last time

#### **Computational MQ problem**

**Given**: m multivariate polynomials  $p_1, p_2, \ldots, p_m \in \mathbb{F}_q[x_1, \ldots, x_n]$  of degree 2

**Find**: (if any) a vector  $(u_1, \ldots, u_n) \in \mathbb{F}_q^n$  such that

$$\begin{cases} p_1(u_1,\ldots,u_n) = 0 \\ p_2(u_1,\ldots,u_n) = 0 \\ \ldots \\ p_m(u_1,\ldots,u_n) = 0 \end{cases}$$

- ► Recall also that traditionally MQ schemes are ad-hoc
  - the hard problem is not the MQ problem, and not only the MQ problem
- ▶ What does it take to get a provably secure MQ scheme?
  - MQDSS: first signature with (lossy) ROM reduction to MQ
  - SOFIA: first signature with (lossy) QROM reduction to MQ

## Some brainstorming in Sofia with Andy and Peter

- ▶ Lack of provable MQ signature
- ▶ Inefficient signatures from 3-pass IDS [Sakumoto et al. '11]
  - big soundness error (2/3)


## Some brainstorming in Sofia with Andy and Peter

- ▶ Lack of provable MQ signature
- ▶ Inefficient signatures from 3-pass IDS [Sakumoto et al. '11]
  - big soundness error (2/3)
- ► Can we gain smth. if we consider signatures from 5-pass IDS?
  - smaller soundness error  $(\frac{q+1}{2q} \text{ over } \mathbb{F}_q) \Rightarrow \text{smaller signatures}$
  - FS transform for 5-pass already available [El Yousfi '12]
    - ▶ loose reduction in the ROM (as for 3-pass [Pointcheval & Stern '96])

## Some brainstorming in Sofia with Andy and Peter

- ▶ Lack of provable MQ signature
- ▶ Inefficient signatures from 3-pass IDS [Sakumoto et al. '11]
  - big soundness error (2/3)
- ► Can we gain smth. if we consider signatures from 5-pass IDS?
  - smaller soundness error  $(\frac{q+1}{2q} \text{ over } \mathbb{F}_q) \Rightarrow \text{smaller signatures}$
  - FS transform for 5-pass already available [El Yousfi '12]
    - ▶ loose reduction in the ROM (as for 3-pass [Pointcheval & Stern '96])


#### **Canonical Identification Schemes**



#### Informally:

- (1) Prover commits to some (randomized) value derived from sk
- (2) Verifier picks a challenge 'ch'
- (3) Prover computes response 'resp'
- (4) Verifier checks if response matches challenge

### **Properties of Canonical 3-pass IDS**



Special soundness


There exists knowledge extractor  ${\cal K}$  s.t. given two valid transcripts:

$$\mathsf{trans} = (\mathsf{com}, \mathsf{ch}, \mathsf{resp}), \ \mathsf{trans}' = (\mathsf{com}, \mathsf{ch}', \mathsf{resp}'), \quad \mathsf{ch} \neq \mathit{ch}',$$


extracts the secret sk with non-negligible probability

 $\blacktriangleright$  (statistical) Honest-Verifier Zero-Knowledge There exists a PPT algorithm  $\mathcal{S}$ , called the simulator, such that the statistical distance between the real transcript and the simulated transcript is negligible in k.


### The Fiat-Shamir transform




### The Fiat-Shamir transform




#### The Fiat-Shamir transform





## FS signature


















$$trans = (com, ch, resp)$$
  
 $trans' = (com, ch', resp')$ 














### **Canonical 5-pass IDS**




### The Fiat-Shamir transform on 5-pass IDS




### The Fiat-Shamir transform on 5-pass IDS




#### FS signature





## Sakumoto-Shirai-Hiwatari 5-pass IDS



- ▶ Smaller soundness error  $(\frac{q+1}{2q} \text{ over } \mathbb{F}_q) \Rightarrow$  smaller signatures
- ► Key technique: cut-and-choose for MQ

- ▶ Smaller soundness error  $(\frac{q+1}{2q} \text{ over } \mathbb{F}_q) \Rightarrow$  smaller signatures
- ► Key technique: cut-and-choose for MQ
- ▶ Bilinear map G(x,y) = F(x+y) F(x) F(y)
  - Split s and F(s) into  $r_0, r_1$  and  $F(r_0), F(r_1)$ 
    - $\blacktriangleright$  Since then  $\textbf{s}=\textbf{r}_0+\textbf{r}_1\Rightarrow \textbf{F}(\textbf{s})=\textbf{G}(\textbf{r}_0,\textbf{r}_1)+\textbf{F}(\textbf{r}_0)+\textbf{F}(\textbf{r}_1)$
  - $\bullet$  Split  $\textbf{r}_0$  and  $\textbf{F}(\textbf{r}_0)$  further into  $\textbf{t}_0,\textbf{t}_1$  resp.  $\textbf{e}_0,\textbf{e}_1$


- ▶ Smaller soundness error  $(\frac{q+1}{2q} \text{ over } \mathbb{F}_q) \Rightarrow$  smaller signatures
- ► Key technique: cut-and-choose for MQ
- ▶ Bilinear map G(x,y) = F(x+y) F(x) F(y)
  - Split s and F(s) into  $r_0, r_1$  and  $F(r_0), F(r_1)$ 
    - $\blacktriangleright$  Since then  $\textbf{s}=\textbf{r}_0+\textbf{r}_1\Rightarrow \textbf{F}(\textbf{s})=\textbf{G}(\textbf{r}_0,\textbf{r}_1)+\textbf{F}(\textbf{r}_0)+\textbf{F}(\textbf{r}_1)$
  - $\bullet$  Split  $\textbf{r}_0$  and  $\textbf{F}(\textbf{r}_0)$  further into  $\textbf{t}_0,\textbf{t}_1$  resp.  $\textbf{e}_0,\textbf{e}_1$

- ▶ Smaller soundness error  $(\frac{q+1}{2q} \text{ over } \mathbb{F}_q) \Rightarrow$  smaller signatures
- ► Key technique: cut-and-choose for MQ
- ▶ Bilinear map G(x,y) = F(x+y) F(x) F(y)
  - Split s and F(s) into  $r_0, r_1$  and  $F(r_0), F(r_1)$ 
    - $\blacktriangleright$  Since then  $\textbf{s}=\textbf{r}_0+\textbf{r}_1\Rightarrow \textbf{F}(\textbf{s})=\textbf{G}(\textbf{r}_0,\textbf{r}_1)+\textbf{F}(\textbf{r}_0)+\textbf{F}(\textbf{r}_1)$
  - Split  $\mathbf{r}_0$  and  $\mathbf{F}(\mathbf{r}_0)$  further into  $\mathbf{t}_0, \mathbf{t}_1$  resp.  $\mathbf{e}_0, \mathbf{e}_1$
  - $r_0 = t_0 + t_1$
  - $F(r_0) = e_0 + e_1$
- $\blacktriangleright$  Using bilinearity,  $\textbf{v} = (\textbf{G}(t_0,\textbf{r}_1) + \textbf{e}_0) + (\textbf{F}(\textbf{r}_1) + \textbf{G}(t_1,\textbf{r}_1) + \textbf{e}_1)$
- ightharpoonup Result: reveal either  $\mathbf{r}_0$  or  $\mathbf{r}_1$ , and  $(\mathbf{t}_1, \mathbf{e}_1)$
- Zero knowledge property satisfied

### Sakumoto et al. 5-pass IDS

#### The extractor K needs 4 valid transcripts!


$$\begin{aligned} &(\mathsf{com}, \mathsf{ch}_1, \mathsf{resp}_1, \mathsf{ch}_2, \mathsf{resp}_2) \\ &(\mathsf{com}, \mathsf{ch}_1, \mathsf{resp}_1, \mathsf{ch}_2', \mathsf{resp}_2') \\ &(\mathsf{com}, \mathsf{ch}_1', \mathsf{resp}_1', \mathsf{ch}_2, \mathsf{resp}_2'') \\ &(\mathsf{com}, \mathsf{ch}_1', \mathsf{resp}_1', \mathsf{ch}_2', \mathsf{resp}_2''') \end{aligned}$$



### Sakumoto et al. 5-pass IDS

#### The extractor K needs 4 valid transcripts!

```
 \begin{aligned} &(\mathsf{com}, \mathsf{ch_1}, \mathsf{resp_1}, \mathsf{ch_2}, \mathsf{resp_2}) \\ &(\mathsf{com}, \mathsf{ch_1}, \mathsf{resp_1}, \mathsf{ch_2}', \mathsf{resp_2'}) \\ &(\mathsf{com}, \mathsf{ch_1}', \mathsf{resp_1}', \mathsf{ch_2}, \mathsf{resp_2''}) \\ &(\mathsf{com}, \mathsf{ch_1}', \mathsf{resp_1}', \mathsf{ch_2}', \mathsf{resp_2'''}) \end{aligned}
```



- ▶ Focus attention on 5-pass IDS with second challenge space  $|ChS_2| = 2$ 
  - Sakumoto et al. 5-pass IDS is such
  - Most in the literature are such

### Next step ...

What is the problem with FS proof in the QROM?

- $\blacktriangleright$  We need to see the signature  $\sigma$  before rewinding
- ▶ We need to see the oracle inputs
- ▶ Seeing (measuring) destroys the quantum state
- ► The proof fails terribly

### Next step ...MQ signatures in the QROM

What is the problem with FS proof in the QROM?

- $\blacktriangleright$  We need **to see** the signature  $\sigma$  before rewinding
- We need to see the oracle inputs
- ► Seeing (measuring) destroys the quantum state
- ► The proof fails terribly

A solution: Unruh transform [Unruh '14] adapted for q2 IDS

- ▶ Online extractability
- ▶ We can extract the witness without rewinding
- Enough transcripts directly available

### Next step ...MQ signatures in the QROM

What is the problem with FS proof in the QROM?

- $\blacktriangleright$  We need **to see** the signature  $\sigma$  before rewinding
- We need to see the oracle inputs
- Seeing (measuring) destroys the quantum state
- ► The proof fails terribly

A solution: Unruh transform [Unruh '14] adapted for q2 IDS

- ▶ Online extractability
- ▶ We can extract the witness without rewinding
- ► Enough transcripts directly available

We proposed SOFIA - MQ signature secure in the QROM

### **MQDSS** vs **SOFIA**

	Sec.	q	n (= m)	r	pk (bytes)	sk (bytes)	Signature (bytes)
MQDSS-31-64 (AC '16)	128 (ROM)	31	48	269	72	64	40952
SOFIA-4-128 (PKC '18)	128 (QROM)	4	128	438	64	32	126176

- ▶ SOFIA still comparable to Picnic (with QROM proof),
- ▶ but much slower than SPHINCS + and lattice based schemes

#### NIST parameter sets MQDSS

	Sec. cat.	q	n (= m)	r	pk (bytes)	sk (bytes)	Signature (bytes)
MQDSS-31-48 (Round 2)	1-2	31	48	135	46	16	20854
MQDSS-31-64 (Round 2)	3-4	31	64	202	64	24	43728

### An attack on MQDSS

- August 2019, Daniel Kales and Greg Zaverucha forgery in approx. 2<sup>95</sup> hash calls for MQDSS-31-48
- ▶ Can be mitigated by  $\approx 1.4 \times (\text{number of rounds})$
- ▶ Proof still valid!
  - Attack is result of not taking into account non-tightness of proof for choosing parameters

### An attack on MQDSS

- ▶ August 2019, Daniel Kales and Greg Zaverucha forgery in approx. 2<sup>95</sup> hash calls for MQDSS-31-48
- ▶ Can be mitigated by  $\approx 1.4 \times (\text{number of rounds})$
- ▶ Proof still valid!
  - Attack is result of not taking into account non-tightness of proof for choosing parameters
- ► New parameters after attack (estimate):

	Sec. cat.	q	n	r	pk	sk	Signature
MQDSS-31-48 (new)	1-2	31	48	184	46B	16B	28400B
MQDSS-31-48 (Round 2)	1-2	31	48	135	46 <b>B</b>	16 <b>B</b>	20854 <b>B</b>
MQDSS-31-64 (new)	3-4	31	64	277	64B	24B	59928B
MQDSS-31-64 (Round 2)	3-4	31	64	202	64 <b>B</b>	24 <b>B</b>	43728 <b>B</b>


## **Developments during the NIST competition**

- ► Fiat-Shamir shown secure in the QROM SOFIA becomes superfluous
- ▶ MQDSS proven secure in the QROM still, sizes are huge
- several approaches that drastically improve the signature size
- ▶ Mudfish [Beullens, Eurocrypt '20]
  - Idea to reduce soundness error by introducing a preprocessing phase with a trusted Helper
  - ullet And then have a regular  $\Sigma$ -protocol (satisfies completeness, special soundness, HVZK)
  - Takes inspiration from SOFIA and MPC-in-the-head [Katz, Kolesnikov, Wang, '18]
- ▶ MEDS, ALTEQ Fiat-Shamir Goldreich-Micali-Wigderson scheme based on variants of Isomorphism of Polynomials
- ▶ MQOM Fiat-Shamir based on MPC-in-the-head paradigm

[Goldreich-Micali-Wigderson '91]:


Let  $\phi$  be an isomorphism s.t.  $\mathcal{O}_1 = \phi(\mathcal{O}_0)$ .






[Goldreich-Micali-Wigderson '91]:


Let  $\phi$  be an isomorphism s.t.  $\mathcal{O}_1 = \phi(\mathcal{O}_0)$ .






[Goldreich-Micali-Wigderson '91]:


Let  $\phi$  be an isomorphism s.t.  $\mathcal{O}_1 = \phi(\mathcal{O}_0)$ .






[Goldreich-Micali-Wigderson '91]:


Let  $\phi$  be an isomorphism s.t.  $\mathcal{O}_1 = \phi(\mathcal{O}_0)$ .






[Goldreich-Micali-Wigderson '91]:


Let  $\phi$  be an isomorphism s.t.  $\mathcal{O}_1 = \phi(\mathcal{O}_0)$ .






[Goldreich-Micali-Wigderson '91]:


Let  $\phi$  be an isomorphism s.t.  $\mathcal{O}_1 = \phi(\mathcal{O}_0)$ .






[Goldreich-Micali-Wigderson '91]:


Let  $\phi$  be an isomorphism s.t.  $\mathcal{O}_1 = \phi(\mathcal{O}_0)$ .






[Goldreich-Micali-Wigderson '91]:


Let  $\phi$  be an isomorphism s.t.  $\mathcal{O}_1 = \phi(\mathcal{O}_0)$ .






[Goldreich-Micali-Wigderson '91]:


Let  $\phi$  be an isomorphism s.t.  $\mathcal{O}_1 = \phi(\mathcal{O}_0)$ .






[Goldreich-Micali-Wigderson '91]:


Let  $\phi$  be an isomorphism s.t.  $\mathcal{O}_1 = \phi(\mathcal{O}_0)$ .






[Goldreich-Micali-Wigderson '91]:

Let  $\phi$  be an isomorphism s.t.  $\mathcal{O}_1 = \phi(\mathcal{O}_0)$ .





### Generic hard equivalence problem $EQ(\mathcal{O}_0, \mathcal{O}_1)$ :

### Generic hard equivalence problem $EQ(\mathcal{O}_0, \mathcal{O}_1)$ :

### Generic hard equivalence problem $EQ(\mathcal{O}_0, \mathcal{O}_1)$ :

Given  $\mathcal{O}_0$  and  $\mathcal{O}_1$ , find (if any) an isomorphism  $\phi$  s.t.  $\mathcal{O}_1 = \phi(\mathcal{O}_0)$ 

▶ Isomorphism of polynomials - Patarin's signature, 1998

### Generic hard equivalence problem $EQ(\mathcal{O}_0, \mathcal{O}_1)$ :

- ▶ **Isomorphism of polynomials** Patarin's signature, 1998
- Quasigroup isotopy Identification scheme, Denes, 2001

Generic hard equivalence problem  $EQ(\mathcal{O}_0, \mathcal{O}_1)$ :

- ▶ Isomorphism of polynomials Patarin's signature, 1998
- ▶ Quasigroup isotopy Identification scheme, Denes, 2001
- ▶ Isogeny on eliptic curves SeaSign 2018, SqiSign 2020, De Feo et al.

Generic hard equivalence problem  $EQ(\mathcal{O}_0, \mathcal{O}_1)$ :

- ▶ Isomorphism of polynomials Patarin's signature, 1998
- Quasigroup isotopy Identification scheme, Denes, 2001
- ▶ **Isogeny on eliptic curves** SeaSign 2018, SqiSign 2020, De Feo et al.
- ▶ Code equivalence LESS Biasse et al. 2020, LESS-FM Barenghi et al. 2021

### Generic hard equivalence problem $EQ(\mathcal{O}_0, \mathcal{O}_1)$ :

- ▶ Isomorphism of polynomials Patarin's signature, 1998
- Quasigroup isotopy Identification scheme, Denes, 2001
- ▶ **Isogeny on eliptic curves** SeaSign 2018, SqiSign 2020, De Feo et al.
- ▶ Code equivalence LESS Biasse et al. 2020, LESS-FM Barenghi et al. 2021
- ▶ Alternate trilinear form equivalence Tang et al. 2022

Generic hard equivalence problem  $EQ(\mathcal{O}_0, \mathcal{O}_1)$ :

- ▶ Isomorphism of polynomials Patarin's signature, 1998
- Quasigroup isotopy Identification scheme, Denes, 2001
- ▶ **Isogeny on eliptic curves** SeaSign 2018, SqiSign 2020, De Feo et al.
- ▶ Code equivalence LESS Biasse et al. 2020, LESS-FM Barenghi et al. 2021
- ▶ Alternate trilinear form equivalence Tang et al. 2022
- ▶ Lattice isomorphism Ducas and van Woerden 2022

Generic hard equivalence problem  $EQ(\mathcal{O}_0, \mathcal{O}_1)$ : Given  $\mathcal{O}_0$  and  $\mathcal{O}_1$ , find (if any) an isomorphism  $\phi$  s.t.  $\mathcal{O}_1 = \phi(\mathcal{O}_0)$ 

- ▶ Isomorphism of polynomials Patarin's signature, 1998
- Quasigroup isotopy Identification scheme, Denes, 2001
- ▶ Isogeny on eliptic curves SeaSign 2018, SqiSign 2020, De Feo et al.
- ▶ Code equivalence LESS Biasse et al. 2020, LESS-FM Barenghi et al. 2021
- ▶ Alternate trilinear form equivalence Tang et al. 2022
- ▶ Lattice isomorphism Ducas and van Woerden 2022
- ▶ Matrix code equivalence with Tung Chou, Ruben Niederhagen, Edoardo Persichetti, Tovohery Hajatiana Randrianarisoa, Lars Ran, Krijn Reijnders, Monika Trimoska , 2022
- **▶** ...

**Matrix code** - a subspace of  $\mathcal{M}_{m \times n}(\mathbb{F}_q)$  of dimension k endowed with **rank metric** 

$$d(\mathbf{A},\mathbf{B}) = \mathsf{Rank}(\mathbf{A} - \mathbf{B})$$

**Matrix code** - a subspace of  $\mathcal{M}_{m\times n}(\mathbb{F}_q)$  of dimension k endowed with rank metric

$$d(\mathbf{A}, \mathbf{B}) = \mathsf{Rank}(\mathbf{A} - \mathbf{B})$$

### Matrix Code Equivalence (MCE) problem [Berger, 2003]

**Input:** Two *k*-dimensional matrix codes  $\mathcal{C}, \mathcal{D} \subset \mathcal{M}_{m,n}(q)$ 

**Question:** Find – if any –  $\mathbf{A} \in GL_m(q)$ ,  $\mathbf{B} \in GL_n(q)$  (an isometry) s.t. for all  $\mathbf{C} \in \mathcal{C}$ , it holds

that

$$\textbf{ACB} \in \mathcal{D}$$

**Matrix code** - a subspace of  $\mathcal{M}_{m\times n}(\mathbb{F}_q)$  of dimension k endowed with rank metric

$$d(\mathbf{A}, \mathbf{B}) = \mathsf{Rank}(\mathbf{A} - \mathbf{B})$$

### Matrix Code Equivalence (MCE) problem [Berger, 2003]

**Input:** Two *k*-dimensional matrix codes  $C, D \subset \mathcal{M}_{m,n}(q)$ 

**Question:** Find – if any –  $\mathbf{A} \in GL_m(q)$ ,  $\mathbf{B} \in GL_n(q)$  (an isometry) s.t. for all  $\mathbf{C} \in \mathcal{C}$ , it holds

that

$$\textbf{ACB} \in \mathcal{D}$$

#### Related problems

► Matrix Codes Right (Left) Equivalence problem (MCRE) – A (B) is trivial

**Matrix code** - a subspace of  $\mathcal{M}_{m \times n}(\mathbb{F}_q)$  of dimension k endowed with **rank metric** 

$$d(\mathbf{A}, \mathbf{B}) = \mathsf{Rank}(\mathbf{A} - \mathbf{B})$$

### Matrix Code Equivalence (MCE) problem [Berger, 2003]

**Input:** Two k-dimensional matrix codes  $\mathcal{C},\mathcal{D}\subset\mathcal{M}_{m,n}(q)$ 

**Question:** Find – if any –  $\mathbf{A} \in GL_m(q)$ ,  $\mathbf{B} \in GL_n(q)$  (an isometry) s.t. for all  $\mathbf{C} \in \mathcal{C}$ , it holds


that

$$\textbf{ACB} \in \mathcal{D}$$

#### Related problems

- ► Matrix Codes Right (Left) Equivalence problem (MCRE) A (B) is trivial
- ▶  $\mathbb{F}_{q^m}$ -linear codes MCE reduces to MCRE

### Known results - relations to other problems



## **Quadratic Maps Linear Equivalence (QMLE) problem**

Introduced by Patarin 1996 as Isomorphism of Polynomials (IP) problem for building an identification scheme and FS signature!

#### Quadratic Maps Linear Equivalence (QMLE) problem

**Input:** Two *k*-tuples of quadratic multivariate polynomials  $\mathcal{F},\ \mathcal{P}\in\mathbb{F}_q[x_1,\ldots,x_n]^k$ 

**Question:** Find – if any – invertible matrices  $\boldsymbol{S}, \boldsymbol{T}$  such that

$$P(x) = TF(Sx).$$

## Quadratic Maps Linear Equivalence (QMLE) problem

Introduced by Patarin 1996 as Isomorphism of Polynomials (IP) problem for building an identification scheme and FS signature!

#### Quadratic Maps Linear Equivalence (QMLE) problem

**Input:** Two *k*-tuples of quadratic multivariate polynomials  $\mathcal{F},\ \mathcal{P}\in\mathbb{F}_q[x_1,\ldots,x_n]^k$ 

**Question:** Find – if any – invertible matrices S, T such that

$$\mathcal{P}(x) = T\mathcal{F}(Sx).$$

#### Related problems

ightharpoonup Isomorphism of Polynomials with one secret (IP1 $\mathcal S$ ), when T is trivial - easy

## Quadratic Maps Linear Equivalence (QMLE) problem

Introduced by Patarin 1996 as Isomorphism of Polynomials (IP) problem for building an identification scheme and FS signature!

#### Quadratic Maps Linear Equivalence (QMLE) problem

**Input:** Two *k*-tuples of quadratic multivariate polynomials  $\mathcal{F},\ \mathcal{P}\in\mathbb{F}_q[x_1,\ldots,x_n]^k$ 

**Question:** Find – if any – invertible matrices  $\boldsymbol{S}, \boldsymbol{T}$  such that

$$P(x) = TF(Sx).$$

#### Related problems

- ▶ Isomorphism of Polynomials with one secret (IP1S), when T is trivial easy
- homogenous version hQMLE hard
- ▶ inhomogenous version easy (heuristic result [FP06])

# Alternating trilinear form equivalence problem (ATFE)

Alternating trilinear form: 
$$\phi(\mathbf{x}, \mathbf{y}, \mathbf{z}) = \sum_{1 \leq i < j < s \leq n} c_{ijs} \begin{vmatrix} x_i & y_i & z_i \\ x_j & y_j & z_j \\ x_s & y_s & z_s \end{vmatrix}$$
 where  $c_{ijs} \in \mathbb{F}_q$ .

▶ Can be stored using  $\binom{n}{3}$  entries: one for each  $c_{ijs}$  coefficient

#### Alternating trilinear form equivalence (ATFE) problem

**Input:** Two alternating trilinear forms  $\phi, \psi \in \mathbb{F}_q[\mathbf{x}, \mathbf{y}, \mathbf{z}]$ .

Question: Find – if any – invertible A such that  $\psi(\mathbf{x},\mathbf{y},\mathbf{z})=\phi(\mathbf{A}\mathbf{x},\mathbf{A}\mathbf{y},\mathbf{A}\mathbf{z}).$ 

# Alternating trilinear form equivalence problem (ATFE)

Alternating trilinear form: 
$$\phi(\mathbf{x}, \mathbf{y}, \mathbf{z}) = \sum_{1 \leq i < j < s \leq n} c_{ijs} \begin{vmatrix} x_i & y_i & z_i \\ x_j & y_j & z_j \\ x_s & y_s & z_s \end{vmatrix}$$
 where  $c_{ijs} \in \mathbb{F}_q$ .

▶ Can be stored using  $\binom{n}{3}$  entries: one for each  $c_{ijs}$  coefficient


#### Alternating trilinear form equivalence (ATFE) problem


**Input:** Two alternating trilinear forms  $\phi, \psi \in \mathbb{F}_q[\mathbf{x}, \mathbf{y}, \mathbf{z}]$ .

Question: Find – if any – invertible A such that  $\psi(\mathbf{x}, \mathbf{y}, \mathbf{z}) = \phi(\mathbf{A}\mathbf{x}, \mathbf{A}\mathbf{y}, \mathbf{A}\mathbf{z})$ .

- ▶ Used by Tang et al. '22 to build a signature scheme with competitive signature sizes
- ▶ Shown to be equivalent to hQMLE (Grochow et al. '21)

### Matrix codes:






### MCE:

▶ matrix codes of rectangular matrices


#### Matrix codes:



### MCE:


- matrix codes of rectangular matrices
- ightharpoonup isometry  $(\mathbf{A},\mathbf{B})$


Systems of polynomials in matrix representation:





### Systems of polynomials in matrix representation:






### hQMLE:

matrix codes of symmetric matrices

Systems of polynomials in matrix representation:




### hQMLE:

- matrix codes of symmetric matrices
- ▶ isometry  $(\mathbf{A}, \mathbf{A}^\top)$

#### MCE, QMLE and ATFE look very similar!

Systems of polynomials in matrix representation:





#### hQMLE:

- matrix codes of symmetric matrices
- ▶ isometry  $(\mathbf{A}, \mathbf{A}^\top)$
- ▶ hQMLE can be seen as MCE, and vice versa

## MCE, QMLE and ATFE look very similar!

Trilinear forms in matrix representation:






#### ATFE:

matrix codes of skew symmetric matrices

We will come back to cryptanalysis of this problem!

#### MCE, QMLE and ATFE look very similar!


Trilinear forms in matrix representation:




#### ATFE:


- matrix codes of skew symmetric matrices
- ▶ isometry  $(\mathbf{A}, \mathbf{A}^\top)$
- ▶ ATFE can be seen as MCE, and as hQMLE (and vice versa)


We will come back to cryptanalysis of this problem!







▶ Challenge space is of size  $2 \Rightarrow$  Soundness error is 1/2







- ▶ Challenge space is of size  $2 \Rightarrow$  Soundness error is 1/2
- ▶ For security of  $\lambda$  bits, needs to be repeated  $r = \lambda$  times!







- ▶ Challenge space is of size  $2 \Rightarrow$  Soundness error is 1/2
- ▶ For security of  $\lambda$  bits, needs to be repeated  $r = \lambda$  times!
- ightharpoonup  $\Rightarrow$  Signature contains  $\lambda$  isometries (from  $\lambda$  rounds)







- ▶ Challenge space is of size  $2 \Rightarrow$  Soundness error is 1/2
- ▶ For security of  $\lambda$  bits, needs to be repeated  $r = \lambda$  times!
- ightharpoonup  $\Rightarrow$  Signature contains  $\lambda$  isometries (from  $\lambda$  rounds)
- $\blacktriangleright \ \Rightarrow$  All operations in signing and verification need to be repeated  $\lambda$  times






▶ Challenge space is now of size  $N \Rightarrow$  Soundness error is 1/N







- ▶ Challenge space is now of size  $N \Rightarrow$  Soundness error is 1/N
- ▶ For security of  $\lambda$  bits, needs to be repeated  $r = \frac{\lambda}{\log N}$  times!





- ▶ Challenge space is now of size  $N \Rightarrow$  Soundness error is 1/N
- ▶ For security of  $\lambda$  bits, needs to be repeated  $r = \frac{\lambda}{\log N}$  times!
- ightharpoonup  $\Rightarrow$  Signature contains  $\frac{\lambda}{\log N}$  isometries







- ▶ Challenge space is now of size  $N \Rightarrow$  Soundness error is 1/N
- ▶ For security of  $\lambda$  bits, needs to be repeated  $r = \frac{\lambda}{\log N}$  times!
- ightharpoonup  $\Rightarrow$  Signature contains  $\frac{\lambda}{\log N}$  isometries
- ightharpoonup  $\Rightarrow$  All operations in signing and verification need to be repeated  $\frac{\lambda}{\log N}$  times







- ▶ Challenge space is now of size  $N \Rightarrow$  Soundness error is 1/N
- ▶ For security of  $\lambda$  bits, needs to be repeated  $r = \frac{\lambda}{\log N}$  times!
- ightharpoonup  $\Rightarrow$  Signature contains  $\frac{\lambda}{\log N}$  isometries
- ightharpoonup  $\Rightarrow$  All operations in signing and verification need to be repeated  $\frac{\lambda}{\log N}$  times
- ► There is a cost N-fold increase in public and private key







- ▶ Challenge space is now of size  $N \Rightarrow$  Soundness error is 1/N
- ▶ For security of  $\lambda$  bits, needs to be repeated  $r = \frac{\lambda}{\log N}$  times!
- ightharpoonup  $\Rightarrow$  Signature contains  $\frac{\lambda}{\log N}$  isometries
- ightharpoonup  $\Rightarrow$  All operations in signing and verification need to be repeated  $\frac{\lambda}{\log N}$  times
- ► There is a cost *N*-fold increase in public and private key
- ► Always necessary to find the best trade-off







▶ The map  $\psi_0$  is chosen at random  $\Rightarrow$  one can include only seed in signature







- lacktriangle The map  $\psi_0$  is chosen at random  $\Rightarrow$  one can include only seed in signature
  - ullet  $\psi_0$  can be reconstructed from the seed







- ▶ The map  $\psi_0$  is chosen at random  $\Rightarrow$  one can include only seed in signature
  - ullet  $\psi_0$  can be reconstructed from the seed
- **Problem:** This works only for ch = 0, and probability of choosing challenge 0 is 1/N







- ▶ The map  $\psi_0$  is chosen at random  $\Rightarrow$  one can include only seed in signature
  - ullet  $\psi_0$  can be reconstructed from the seed
- **Problem:** This works only for ch = 0, and probability of choosing challenge 0 is 1/N
  - ⇒ not a big benefit in general







- ▶ The map  $\psi_0$  is chosen at random  $\Rightarrow$  one can include only seed in signature
  - ullet  $\psi_0$  can be reconstructed from the seed
- **Problem:** This works only for ch = 0, and probability of choosing challenge 0 is 1/N
  - ⇒ not a big benefit in general
  - ⇒ signature is not of constant size







- ▶ The map  $\psi_0$  is chosen at random  $\Rightarrow$  one can include only seed in signature
  - ullet  $\psi_0$  can be reconstructed from the seed
- **Problem:** This works only for ch = 0, and probability of choosing challenge 0 is 1/N
  - ⇒ not a big benefit in general
  - ⇒ signature is not of constant size
- ▶ Idea: Always have a fixed number *M* of 0 challenges







- ▶ The map  $\psi_0$  is chosen at random  $\Rightarrow$  one can include only seed in signature
  - ullet  $\psi_0$  can be reconstructed from the seed
- **Problem:** This works only for ch = 0, and probability of choosing challenge 0 is 1/N
  - ⇒ not a big benefit in general
  - ⇒ signature is not of constant size
- $\blacktriangleright$  Idea: Always have a fixed number M of 0 challenges
  - We need a special hash function that always produces fixed weight outputs





- ▶ The map  $\psi_0$  is chosen at random  $\Rightarrow$  one can include only seed in signature
  - ullet  $\psi_0$  can be reconstructed from the seed
- **Problem:** This works only for ch = 0, and probability of choosing challenge 0 is 1/N
  - ⇒ not a big benefit in general
  - ⇒ signature is not of constant size
- ▶ Idea: Always have a fixed number *M* of 0 challenges
  - We need a special hash function that always produces fixed weight outputs
  - Always necessary to find the best trade-off





- ▶ The map  $\psi_0$  is chosen at random  $\Rightarrow$  one can include only seed in signature
  - ullet  $\psi_0$  can be reconstructed from the seed
- **Problem:** This works only for ch = 0, and probability of choosing challenge 0 is 1/N
  - ⇒ not a big benefit in general
  - ⇒ signature is not of constant size
- ▶ Idea: Always have a fixed number *M* of 0 challenges
  - We need a special hash function that always produces fixed weight outputs
  - Always necessary to find the best trade-off

#### So how better are these schemes in terms of performance?

#### For example, MEDS:

MEDS	q	n (≈ m)	r	pk (bytes)	Signature (bytes)
level 1	4093	25	144	21595	5456
level 2	4093	34	208	55520	10786
level 3	4093	44	272	122000	21052

#### Important to note:

- QMLE/MCE still not so well understood
- Not NP-hard but likely still hard
- ▶ Secure practical parameters significantly changed in the last few years, as our understanding improved

# **Solving matrix code equivalence**

problems

# Solving matrix code equivalence problems

#### Several approaches:

► Graph-based techniques

## Solving matrix code equivalence problems

#### Several approaches:

- ▶ Graph-based techniques
- ► Algebraic models

# Solving matrix code equivalence problems

#### Several approaches:

- ► Graph-based techniques
- ► Algebraic models
- ▶ Leon-like approach (graph-based+algebraic)

ightharpoonup [Faugére, Peret, 2006] – inhomogenous version is easy ( $\mathcal{O}(n^9)$  heuristically)

- ▶ [Faugére, Peret, 2006] inhomogenous version is easy ( $\mathcal{O}(n^9)$  heuristically)
- ▶ [Bouillaguet, Fouque & Véber, 2013] **Graph based approach**  $\mathcal{O}(q^{\frac{2}{3}n}n^9)$

- ▶ [Faugére, Peret, 2006] inhomogenous version is easy ( $\mathcal{O}(n^9)$  heuristically)
- ▶ [Bouillaguet, Fouque & Véber, 2013] **Graph based approach**  $\mathcal{O}(q^{\frac{2}{3}n}n^9)$ 
  - ullet Crucial observation: One collision point ullet = aS turns a hard homogenous instance into easy inhomogenous one

- ▶ [Faugére, Peret, 2006] inhomogenous version is easy  $(\mathcal{O}(n^9)$  heuristically)
- ▶ [Bouillaguet, Fouque & Véber, 2013] Graph based approach  $\mathcal{O}(q^{\frac{2}{3}n}n^9)$ 
  - ullet Crucial observation: One collision point ullet = aS turns a hard homogenous instance into easy inhomogenous one

if 
$$\mathbf{b} = \mathbf{aS}$$
, then  $\mathcal{P}(\mathbf{x} + \mathbf{a}) = \mathcal{F}(\mathbf{xS} + \mathbf{b})\mathbf{T}$ .

- ▶ [Faugére, Peret, 2006] inhomogenous version is easy  $(\mathcal{O}(n^9)$  heuristically)
- ▶ [Bouillaguet, Fouque & Véber, 2013] Graph based approach  $\mathcal{O}(q^{\frac{2}{3}n}n^9)$ 
  - Crucial observation: One collision point b = aS turns a hard homogenous instance into easy inhomogenous one

```
if \mathbf{b} = \mathbf{aS}, then \mathcal{P}(\mathbf{x} + \mathbf{a}) = \mathcal{F}(\mathbf{xS} + \mathbf{b})\mathbf{T}.

\Rightarrow \mathcal{P}'(\mathbf{x}) = \mathcal{P}(\mathbf{x} + \mathbf{a}), \mathcal{F}'(\mathbf{x}) = \mathcal{F}(\mathbf{x} + \mathbf{b}) is easy instance!
```

- ▶ [Faugére, Peret, 2006] inhomogenous version is easy  $(\mathcal{O}(n^9)$  heuristically)
- ▶ [Bouillaguet, Fouque & Véber, 2013] **Graph based approach**  $\mathcal{O}(q^{\frac{2}{3}n}n^9)$ 
  - ullet Crucial observation: One collision point ullet = aS turns a hard homogenous instance into easy inhomogenous one

```
if \mathbf{b} = \mathbf{aS}, then \mathcal{P}(\mathbf{x} + \mathbf{a}) = \mathcal{F}(\mathbf{xS} + \mathbf{b})\mathbf{T}.

\Rightarrow \mathcal{P}'(\mathbf{x}) = \mathcal{P}(\mathbf{x} + \mathbf{a}), \mathcal{F}'(\mathbf{x}) = \mathcal{F}(\mathbf{x} + \mathbf{b}) is easy instance!
```

Problem is reduced to finding the collision

# Algebraic modelling of MCE - the straightforward way

For  $(\mathbf{C}^{(1)},\ldots,\mathbf{C}^{(k)})$  and  $(\mathbf{D}^{(1)},\ldots,\mathbf{D}^{(k)})$  bases of  $\mathcal{C}$  and  $\mathcal{D}$ , find invertible  $\mathbf{A},\mathbf{B}$  and  $\mathbf{T}=(t_{ij})$  s.t.:

$$\sum_{1 \le s \le k} t_{rs} \mathbf{D}^{(s)} = \mathbf{AC}^{(r)} \mathbf{B}, \quad \forall r, 1 \leqslant r \leqslant k$$

# Algebraic modelling of MCE - the straightforward way

For  $(\mathbf{C}^{(1)},\ldots,\mathbf{C}^{(k)})$  and  $(\mathbf{D}^{(1)},\ldots,\mathbf{D}^{(k)})$  bases of  $\mathcal{C}$  and  $\mathcal{D}$ , find invertible  $\mathbf{A},\mathbf{B}$  and  $\mathbf{T}=(t_{ij})$  s.t.:

$$\sum_{1\leqslant s\leqslant k}t_{rs}\mathbf{D}^{(s)}=\mathbf{AC}^{(r)}\mathbf{B},\ \forall r,1\leqslant r\leqslant k$$

▶ Directly: bilinear system of knm eqns in  $m^2 + n^2 + k^2$  vars (bilinear  $a_{ij}b_{i'j'}$ , linear  $t_{rs}$ )

# Algebraic modelling of MCE - the straightforward way

For  $(\mathbf{C}^{(1)},\ldots,\mathbf{C}^{(k)})$  and  $(\mathbf{D}^{(1)},\ldots,\mathbf{D}^{(k)})$  bases of  $\mathcal{C}$  and  $\mathcal{D}$ , find invertible  $\mathbf{A},\mathbf{B}$  and  $\mathbf{T}=(t_{ij})$  s.t.:

$$\sum_{1\leqslant s\leqslant k}t_{rs}\mathbf{D}^{(s)}=\mathbf{AC}^{(r)}\mathbf{B},\ \forall r,1\leqslant r\leqslant k$$

- ▶ Directly: bilinear system of knm eqns in  $m^2 + n^2 + k^2$  vars (bilinear  $a_{ij}b_{i'j'}$ , linear  $t_{rs}$ )
  - Security estimates too high

For  $(\mathbf{C}^{(1)},\ldots,\mathbf{C}^{(k)})$  and  $(\mathbf{D}^{(1)},\ldots,\mathbf{D}^{(k)})$  bases of  $\mathcal{C}$  and  $\mathcal{D}$ , find invertible  $\mathbf{A},\mathbf{B}$  and  $\mathbf{T}=(t_{ij})$  s.t.:

$$\sum_{1\leqslant s\leqslant k}t_{rs}\mathsf{D}^{(s)}=\mathsf{AC}^{(r)}\mathsf{B},\ \ orall r,1\leqslant r\leqslant k$$

- **Directly:** bilinear system of *knm* eqns in  $m^2 + n^2 + k^2$  vars (bilinear  $a_{ij}b_{i'j'}$ , linear  $t_{rs}$ )
  - Security estimates too high
- ▶ Coefs of  $\mathbf{A}_{i_{-}}$  and  $\mathbf{A}_{j_{-}}$  ( $\mathbf{B}_{-i}$  and  $\mathbf{B}_{-j}$ ) don't appear in same equation

For  $(\mathbf{C}^{(1)},\ldots,\mathbf{C}^{(k)})$  and  $(\mathbf{D}^{(1)},\ldots,\mathbf{D}^{(k)})$  bases of  $\mathcal{C}$  and  $\mathcal{D}$ , find invertible  $\mathbf{A},\mathbf{B}$  and  $\mathbf{T}=(t_{ij})$  s.t.:

$$\sum_{1\leqslant s\leqslant k}t_{rs}\mathsf{D}^{(s)}=\mathsf{AC}^{(r)}\mathsf{B},\ \ \forall r,1\leqslant r\leqslant k$$

- ▶ **Directly:** bilinear system of *knm* eqns in  $m^2 + n^2 + k^2$  vars (bilinear  $a_{ij}b_{i'j'}$ , linear  $t_{rs}$ )
  - Security estimates too high
- ▶ Coefs of  $A_{i_-}$  and  $A_{j_-}$  ( $B_{-i}$  and  $B_{-j}$ ) don't appear in same equation
- ▶ Consider only a small number  $\alpha$  of rows of A, i.e.,

$$\sum_{1 \leq s \leq k} t_{rs} \mathbf{D}_{i}^{(s)} = \mathbf{A}_{i} \mathbf{C}^{(r)} \mathbf{B}, \quad \forall r, i, \ 1 \leqslant r \leqslant k, \ 1 \leqslant i \leqslant \alpha.$$

For  $(\mathbf{C}^{(1)},\ldots,\mathbf{C}^{(k)})$  and  $(\mathbf{D}^{(1)},\ldots,\mathbf{D}^{(k)})$  bases of  $\mathcal{C}$  and  $\mathcal{D}$ , find invertible  $\mathbf{A},\mathbf{B}$  and  $\mathbf{T}=(t_{ij})$  s.t.:

$$\sum_{1\leqslant s\leqslant k}t_{rs}\mathsf{D}^{(s)}=\mathsf{AC}^{(r)}\mathsf{B},\ \ orall r,1\leqslant r\leqslant k$$

- ▶ Directly: bilinear system of knm eqns in  $m^2 + n^2 + k^2$  vars (bilinear  $a_{ij}b_{i'j'}$ , linear  $t_{rs}$ )
  - Security estimates too high
- ▶ Coefs of  $A_{i_-}$  and  $A_{j_-}$  ( $B_{-i}$  and  $B_{-j}$ ) don't appear in same equation
- ▶ Consider only a small number  $\alpha$  of rows of A, i.e.,

$$\sum_{1\leqslant s\leqslant k} t_{rs} \mathbf{D}_{i_{-}}^{(s)} = \mathbf{A}_{i_{-}} \mathbf{C}^{(r)} \mathbf{B}, \quad \forall r, i, \ 1\leqslant r\leqslant k, \ 1\leqslant i\leqslant \alpha.$$

▶ Guess  $\alpha m$  coefs of  $A_{i_-}$ , and solve linear system of  $\alpha kn$  equations in  $n^2 + k^2$  variables

For  $(\mathbf{C}^{(1)},\ldots,\mathbf{C}^{(k)})$  and  $(\mathbf{D}^{(1)},\ldots,\mathbf{D}^{(k)})$  bases of  $\mathcal{C}$  and  $\mathcal{D}$ , find invertible  $\mathbf{A},\mathbf{B}$  and  $\mathbf{T}=(t_{ij})$  s.t.:

$$\sum_{1\leqslant s\leqslant k}t_{rs}\mathsf{D}^{(s)}=\mathsf{AC}^{(r)}\mathsf{B},\ \ orall r,1\leqslant r\leqslant k$$

- **Directly:** bilinear system of knm eqns in  $m^2 + n^2 + k^2$  vars (bilinear  $a_{ij}b_{i'j'}$ , linear  $t_{rs}$ )
  - Security estimates too high
- ▶ Coefs of  $A_{i_-}$  and  $A_{j_-}$  ( $B_{-i}$  and  $B_{-j}$ ) don't appear in same equation
- ▶ Consider only a small number  $\alpha$  of rows of A, i.e.,

$$\sum_{1\leqslant s\leqslant k} t_{rs} \mathbf{D}_{i_{-}}^{(s)} = \mathbf{A}_{i_{-}} \mathbf{C}^{(r)} \mathbf{B}, \quad \forall r, i, \ 1\leqslant r\leqslant k, \ 1\leqslant i\leqslant \alpha.$$

- ▶ Guess  $\alpha m$  coefs of  $\mathbf{A}_{i.}$ , and solve linear system of  $\alpha kn$  equations in  $n^2 + k^2$  variables
- ▶ For m = n = k,  $\alpha = 2$  is enough  $\rightarrow$  complexity is  $\mathcal{O}(q^{2n}n^6)$

### Make use of coding theory!

▶ **G** and **G**' – the  $k \times mn$  generator matrices of C and D

- ▶ **G** and **G**' the  $k \times mn$  generator matrices of  $\mathcal C$  and  $\mathcal D$ 
  - "Flatten" the matrices into vectors

- ▶ **G** and **G**' the  $k \times mn$  generator matrices of  $\mathcal C$  and  $\mathcal D$ 
  - "Flatten" the matrices into vectors
- $\blacktriangleright~\mathbf{G}'^{\perp}$  the generator matrix of the dual code of  $\mathcal D$

- ▶ **G** and **G**' the  $k \times mn$  generator matrices of  $\mathcal C$  and  $\mathcal D$ 
  - "Flatten" the matrices into vectors
- $ightharpoonup \mathbf{G}'^{\perp}$  the generator matrix of the dual code of  $\mathcal{D}$
- ▶ Take  $\tilde{G}(A, B)$  generator matrix of ACB (i.e. D) for A and B with unknown coefficients

#### Make use of coding theory!

- ▶ **G** and **G**' the  $k \times mn$  generator matrices of C and D
  - "Flatten" the matrices into vectors
- $ightharpoonup \mathbf{G}'^{\perp}$  the generator matrix of the dual code of  $\mathcal D$
- ightharpoonup Take  $ilde{\textbf{G}}(\textbf{A},\textbf{B})$  generator matrix of  $\textbf{A}\mathcal{C}\textbf{B}$  (i.e.  $\mathcal{D}$ ) for A and B with unknown coefficients
- ► Construct the system:

$$\mathbf{G}'^{\perp} \cdot \tilde{\mathbf{G}}(\mathbf{A}, \mathbf{B})^{\top} = \mathbf{0},$$

of (mn - k)k bilinear equations in only  $m^2 + n^2$  variables

#### Make use of coding theory!

- ▶ **G** and **G**' the  $k \times mn$  generator matrices of C and D
  - "Flatten" the matrices into vectors
- ightharpoonup the generator matrix of the dual code of  ${\cal D}$
- ightharpoonup Take  $ilde{\textbf{G}}(\textbf{A},\textbf{B})$  generator matrix of  $\textbf{A}\mathcal{C}\textbf{B}$  (i.e.  $\mathcal{D}$ ) for A and B with unknown coefficients
- ► Construct the system:

$$\mathbf{G}'^{\perp} \cdot \tilde{\mathbf{G}}(\mathbf{A}, \mathbf{B})^{\top} = \mathbf{0},$$

of (mn - k)k bilinear equations in only  $m^2 + n^2$  variables

- we got rid of t<sup>2</sup> variables!
- ▶ Solve system with Bilinear XL for example

#### Make use of coding theory!

- ▶ **G** and **G**' the  $k \times mn$  generator matrices of C and D
  - "Flatten" the matrices into vectors
- $ightharpoonup \mathbf{G}'^{\perp}$  the generator matrix of the dual code of  $\mathcal D$
- ▶ Take  $\tilde{G}(A, B)$  generator matrix of ACB (i.e. D) for A and B with unknown coefficients
- ► Construct the system:


$$\mathbf{G}'^{\perp} \cdot \tilde{\mathbf{G}}(\mathbf{A}, \mathbf{B})^{\top} = \mathbf{0},$$


of (mn - k)k bilinear equations in only  $m^2 + n^2$  variables


- we got rid of  $t^2$  variables!
- ▶ Solve system with Bilinear XL for example
- ▶ Dimension of code crucial for complexity
  - smallest for k = mn/2, and grows as k reduces or grows

$$\mathcal{C}(\mathbf{A}\mathbf{x},\mathbf{B}\mathbf{y},\mathbf{T}\mathbf{z})=\mathcal{D}(\mathbf{x},\mathbf{y},\mathbf{z})$$


$$\mathcal{C}(\mathbf{A}\mathbf{x},\mathbf{B}\mathbf{y},\mathbf{T}\mathbf{z})=\mathcal{D}(\mathbf{x},\mathbf{y},\mathbf{z})$$









$$\mathcal{C}(\mathbf{A}\mathbf{x},\mathbf{B}\mathbf{y},\mathbf{T}\mathbf{z})=\mathcal{D}(\mathbf{x},\mathbf{y},\mathbf{z})$$



$$\mathcal{C}(\mathsf{Ax},\mathsf{By},\mathsf{z})=\mathcal{D}(\mathsf{x},\mathsf{y},\mathsf{T}^{-1}\mathsf{z})$$




$$\mathcal{C}(\mathsf{x},\mathsf{B}\mathsf{y},\mathsf{T}\mathsf{z})=\mathcal{D}(\mathsf{A}^{-1}\mathsf{x},\mathsf{y},\mathsf{z})$$




$$\mathcal{C}(\mathbf{x},\mathbf{B}\mathbf{y},\mathbf{T}\mathbf{z}) = \mathcal{D}(\mathbf{A}^{-1}\mathbf{x},\mathbf{y},\mathbf{z}) \qquad \qquad \mathcal{C}(\mathbf{A}\mathbf{x},\mathbf{y},\mathbf{T}\mathbf{z}) = \mathcal{D}(\mathbf{x},\mathbf{B}^{-1}\mathbf{y},\mathbf{z})$$


$$\mathcal{C}(\mathbf{A}\mathbf{x},\mathbf{B}\mathbf{y},\mathbf{T}\mathbf{z})=\mathcal{D}(\mathbf{x},\mathbf{y},\mathbf{z})$$



$$\begin{split} \mathcal{C}(\mathbf{A}\mathbf{x},\mathbf{B}\mathbf{y},\mathbf{z}) &= \mathcal{D}(\mathbf{x},\mathbf{y},\mathbf{T}^{-1}\mathbf{z}) \\ \mathbf{G}_{\mathbf{z}}^{\prime\perp} \cdot \tilde{\mathbf{G}}_{\mathbf{z}}^{\top}(\mathbf{A},\mathbf{B}) &= \mathbf{0}, \end{split}$$




$$\mathcal{C}(\mathsf{x},\mathsf{B}\mathsf{y},\mathsf{Tz})=\mathcal{D}(\mathsf{A}^{-1}\mathsf{x},\mathsf{y},\mathsf{z})$$




$$\mathcal{C}(\mathsf{Ax},\mathsf{y},\mathsf{Tz}) = \mathcal{D}(\mathsf{x},\mathsf{B}^{-1}\mathsf{y},\mathsf{z})$$


$$\mathcal{C}(\mathbf{A}\mathbf{x},\mathbf{B}\mathbf{y},\mathbf{T}\mathbf{z})=\mathcal{D}(\mathbf{x},\mathbf{y},\mathbf{z})$$



$$\begin{split} \mathcal{C}(\mathbf{A}\mathbf{x},\mathbf{B}\mathbf{y},\mathbf{z}) &= \mathcal{D}(\mathbf{x},\mathbf{y},\mathbf{T}^{-1}\mathbf{z}) \\ \mathbf{G}_{\mathbf{z}}^{\prime\perp} \cdot \tilde{\mathbf{G}}_{\mathbf{z}}^{\top}(\mathbf{A},\mathbf{B}) &= \mathbf{0}, \end{split}$$




$$\begin{split} \mathcal{C}(\mathbf{x},\mathbf{B}\mathbf{y},\mathbf{T}\mathbf{z}) &= \mathcal{D}(\mathbf{A}^{-1}\mathbf{x},\mathbf{y},\mathbf{z}) \\ \mathbf{G}_{\mathbf{x}}^{\prime\perp} \cdot \tilde{\mathbf{G}}_{\mathbf{x}}^{\top}(\mathbf{B},\mathbf{T}) &= \mathbf{0}, \end{split}$$




$$\mathcal{C}(\mathbf{A}\mathbf{x},\mathbf{y},\mathbf{T}\mathbf{z}) = \mathcal{D}(\mathbf{x},\mathbf{B}^{-1}\mathbf{y},\mathbf{z})$$


$$\mathcal{C}(\mathbf{A}\mathbf{x},\mathbf{B}\mathbf{y},\mathbf{T}\mathbf{z})=\mathcal{D}(\mathbf{x},\mathbf{y},\mathbf{z})$$



$$\begin{split} \mathcal{C}(\mathbf{A}\mathbf{x},\mathbf{B}\mathbf{y},\mathbf{z}) &= \mathcal{D}(\mathbf{x},\mathbf{y},\mathbf{T}^{-1}\mathbf{z}) \\ \mathbf{G}_{\mathbf{z}}^{\prime\perp} \cdot \tilde{\mathbf{G}}_{\mathbf{z}}^{\top}(\mathbf{A},\mathbf{B}) &= \mathbf{0}, \end{split}$$




$$\begin{split} \mathcal{C}(\textbf{x},\textbf{B}\textbf{y},\textbf{T}\textbf{z}) &= \mathcal{D}(\textbf{A}^{-1}\textbf{x},\textbf{y},\textbf{z}) \\ \textbf{G}_{\textbf{x}}^{\prime\perp} \cdot \tilde{\textbf{G}}_{\textbf{x}}^{\top}(\textbf{B},\textbf{T}) &= \textbf{0}, \end{split}$$




$$\begin{split} \mathcal{C}(\mathbf{A}\mathbf{x},\mathbf{y},\mathbf{T}\mathbf{z}) &= \mathcal{D}(\mathbf{x},\mathbf{B}^{-1}\mathbf{y},\mathbf{z}) \\ \mathbf{G}_{\mathbf{y}}'^{\perp} \cdot \tilde{\mathbf{G}}_{\mathbf{y}}^{\top}(\mathbf{A},\mathbf{T}) &= \mathbf{0}, \end{split}$$


$$\mathcal{C}(\mathsf{Ax},\mathsf{By},\mathsf{Tz}) = \mathcal{D}(\mathsf{x},\mathsf{y},\mathsf{z})$$



$$\begin{split} \mathcal{C}(\mathbf{A}\mathbf{x},\mathbf{B}\mathbf{y},\mathbf{z}) &= \mathcal{D}(\mathbf{x},\mathbf{y},\mathbf{T}^{-1}\mathbf{z}) \\ \mathbf{G}_{\mathbf{z}}^{\prime\perp} \cdot \tilde{\mathbf{G}}_{\mathbf{z}}^{\top}(\mathbf{A},\mathbf{B}) &= \mathbf{0}, \end{split}$$



$$\begin{split} \mathcal{C}(\mathbf{x}, \mathbf{B}\mathbf{y}, \mathbf{T}\mathbf{z}) &= \mathcal{D}(\mathbf{A}^{-1}\mathbf{x}, \mathbf{y}, \mathbf{z}) \\ \mathbf{G}_{\mathbf{x}}^{\prime \perp} \cdot \tilde{\mathbf{G}}_{\mathbf{x}}^{\top}(\mathbf{B}, \mathbf{T}) &= \mathbf{0}, \end{split}$$



$$\begin{split} \mathcal{C}(\mathbf{A}\mathbf{x},\mathbf{y},\mathbf{T}\mathbf{z}) &= \mathcal{D}(\mathbf{x},\mathbf{B}^{-1}\mathbf{y},\mathbf{z}) \\ \mathbf{G}_{\mathbf{y}}^{\prime\perp} \cdot \tilde{\mathbf{G}}_{\mathbf{y}}^{\top}(\mathbf{A},\mathbf{T}) &= \mathbf{0}, \end{split}$$

$$\mathbf{G}_{\mathbf{z}}^{\prime\perp}\cdot\tilde{\mathbf{G}}_{\mathbf{z}}^{\top}(\mathbf{A},\mathbf{B})=\mathbf{0},\tag{1}$$

$$\mathbf{G}_{\mathbf{x}}^{\prime\perp}\cdot\tilde{\mathbf{G}}_{\mathbf{x}}^{\top}(\mathbf{B},\mathbf{T})=\mathbf{0},$$
 (2)

$$\mathbf{G}_{\mathbf{y}}^{\prime\perp}\cdot\tilde{\mathbf{G}}_{\mathbf{y}}^{\top}(\mathbf{A},\mathbf{T})=\mathbf{0}.\tag{3}$$

▶ A total of (mn - k)k + (nk - m)m + (mk - n)n equations in  $n^2 + m^2 + k^2$  variables

$$\mathbf{G}_{\mathbf{z}}^{\prime\perp}\cdot\tilde{\mathbf{G}}_{\mathbf{z}}^{\top}(\mathbf{A},\mathbf{B})=\mathbf{0},\tag{1}$$

$$\mathbf{G}_{\mathbf{x}}^{\prime\perp}\cdot\tilde{\mathbf{G}}_{\mathbf{x}}^{\top}(\mathbf{B},\mathbf{T})=\mathbf{0},\tag{2}$$

$$\mathbf{G}_{\mathbf{y}}^{\prime\perp}\cdot\tilde{\mathbf{G}}_{\mathbf{y}}^{\top}(\mathbf{A},\mathbf{T})=\mathbf{0}.\tag{3}$$

- ▶ A total of (mn k)k + (nk m)m + (mk n)n equations in  $n^2 + m^2 + k^2$  variables
- ► The system is not semi-regular though!
  - Syzygies in degree 3 from linear combination of types  $t_{ij} \cdot (1)$ ,  $a_{ij} \cdot (2)$ ,  $b_{ij} \cdot (3)$

$$\mathbf{G}_{\mathbf{z}}^{\prime\perp}\cdot\tilde{\mathbf{G}}_{\mathbf{z}}^{\top}(\mathbf{A},\mathbf{B})=\mathbf{0},\tag{1}$$

$$\mathbf{G}_{\mathsf{x}}^{\prime\perp}\cdot\tilde{\mathbf{G}}_{\mathsf{x}}^{\top}(\mathsf{B},\mathsf{T})=\mathbf{0},\tag{2}$$

$$\mathbf{G}_{\mathbf{y}}^{\prime\perp}\cdot\tilde{\mathbf{G}}_{\mathbf{y}}^{\top}(\mathbf{A},\mathbf{T})=\mathbf{0}.\tag{3}$$

- ▶ A total of (mn k)k + (nk m)m + (mk n)n equations in  $n^2 + m^2 + k^2$  variables
- The system is not semi-regular though!
  - Syzygies in degree 3 from linear combination of types  $t_{ij} \cdot (1)$ ,  $a_{ij} \cdot (2)$ ,  $b_{ij} \cdot (3)$
- ▶ We can estimate the Hilbert series and complexity for solving using Bilinear XL

$$\mathbf{G}_{\mathbf{z}}^{\prime\perp}\cdot\tilde{\mathbf{G}}_{\mathbf{z}}^{\top}(\mathbf{A},\mathbf{B})=\mathbf{0},\tag{1}$$

$$\mathbf{G}_{\mathbf{x}}^{\prime\perp}\cdot\tilde{\mathbf{G}}_{\mathbf{x}}^{\top}(\mathbf{B},\mathbf{T})=\mathbf{0},\tag{2}$$

$$\mathbf{G}_{\mathbf{y}}^{\prime\perp}\cdot\tilde{\mathbf{G}}_{\mathbf{y}}^{\top}(\mathbf{A},\mathbf{T})=\mathbf{0}.\tag{3}$$

- ▶ A total of (mn k)k + (nk m)m + (mk n)n equations in  $n^2 + m^2 + k^2$  variables
- ► The system is not semi-regular though!
  - Syzygies in degree 3 from linear combination of types  $t_{ij} \cdot (1)$ ,  $a_{ij} \cdot (2)$ ,  $b_{ij} \cdot (3)$
- ▶ We can estimate the Hilbert series and complexity for solving using Bilinear XL

n = m = k	plain	improved
14	169	148
22	255	218
30	349	299
30	349	299

### **Summary of the course**

- Monday Designs
  - General
  - Classic designs
- ► Tuesday Design and general MQ solving techniques
  - Key size optimization techniques
  - Algorithms for solving the MQ problem
- Wednesday Cryptanalysis
  - MinRank
  - Equivalent keys attacks
- ► Thursday Cryptanalysis
  - Attacks on UOV
- ► Friday Provably secure designs
  - Fiat-Shamir signatures MQDSS, SOFIA, MEDS

Thank you for listening!

And attending this course!